

# Flexible CCS Tracer Wire PE30

[agavewire.com/products/tracer-wire/open-trench-open-cut/flexible-ccs-tracer-wire/flexible-ccs-tracer-pe30-ul](http://agavewire.com/products/tracer-wire/open-trench-open-cut/flexible-ccs-tracer-wire/flexible-ccs-tracer-pe30-ul)

[Home](#) » [Products](#) » [Tracer Wire](#) » [Open Trench-Open Cut](#) » [Flexible CCS](#) » PE30 UL

**Conductor:**

Copper Clad Steel

**Stranding:**

Solid

**Insulation:**

PE UL .030" Nominal Wall

**Temperature Rating:**

-20°C to +80°C

**Color:**

Any color available

**Compliances:**

UL Listed

**Standard Reel Size:**

500' or 2500' reels

Other put-ups available upon request

Also available in [PE45](#)



**Flexible CCS Tracer PE30 UL Product Data Sheet**

Part Number	AWG	Nom. Weight LBS/M'	Nom. Copper OD	Nom. Diam.	DC Resist @20°C	Break Load
APCS-1801	18	7.17	.0403"	0.102"	30.41	70
APCS-1601	16	10.14	.0508"	0.112"	19.14	111
APCS-1401	14	15.07	.0641"	0.126"	12.02	177
APCS-1201	12	22.36	.0808"	0.142"	7.57	282
APCS-1001	10	33.93	.1019"	0.164"	4.76	449
APCS-0801	8	51.89	.1285"	0.190"	2.99	713
APCS-0601	6	78.85	.1620"	0.222"	1.88	1000

