

BRASS PEX FITTINGS | 90° ELBOW


Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
90 DEGREE ELBOW					
H60069	HPPEXLF9012	1/2" PEX x 1/2" PEX 90° ELBOW	25	800	<input type="checkbox"/>
H60070	HPPEXLF903412	3/4" PEX x 1/2" PEX 90° ELBOW	25	400	<input type="checkbox"/>
H60071	HPPEXLF9034	3/4" PEX x 3/4" PEX 90° ELBOW	25	400	<input type="checkbox"/>
H60072	HPPEXLF901	1" PEX x 1" PEX 90° ELBOW	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada


Maximum temperature (no pressure): **Maximum working temperature/pressure:**

320°F (160°C)

320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act (Sec. 1417) ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:
JOB LOCATION:
CONTRACTOR:
DATE:
ITEM TAG:
ENGINEER APPROVAL:
DATE:
PART NUMBER:
www.hydrapro.biz | (800) 849-4844 | Fax (877) 249-8435

Atlanta (GA) • Dallas (TX) • Houston (TX) • Pompano Beach (FL) • Jackson (MI)

BRASS PEX FITTINGS | DROP EAR 90° ELBOW



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
DROP EAR 90 DEGREE ELBOW					
H60050	HPPEXLFDE9012	1/2" PEX x 1/2" FIP DROP EAR 90° ELBOW	25	800	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): **Maximum working temperature/pressure:**

320°F (160°C)

320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | COUPLING


Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
COUPLING					
H60054	HPPEXLC12	1/2" PEX x 1/2" PEX COUPLING	25	800	<input type="checkbox"/>
H60055	HPPEXLC3412	3/4" PEX x 1/2" PEX COUPLING	25	400	<input type="checkbox"/>
H60056	HPPEXLC34	3/4" PEX x 3/4" PEX COUPLING	25	400	<input type="checkbox"/>
H60058	HPPEXLC134	1" PEX x 3/4" PEX COUPLING	5	120	<input type="checkbox"/>
H60057	HPPEXLC1	1" PEX x 1" PEX COUPLING	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada


Maximum temperature (no pressure): **Maximum working temperature/pressure:**

320°F (160°C)

320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:
JOB LOCATION:
CONTRACTOR:
DATE:
ITEM TAG:
ENGINEER APPROVAL:
DATE:
PART NUMBER:

BRASS PEX FITTINGS | TEE



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
TEE					
H60059	HPPEXLFT12	1/2" PEX x 1/2" PEX x 1/2" PEX TEE	25	800	<input type="checkbox"/>
H60060	HPPEXLFT121234	1/2" PEX x 1/2" PEX x 3/4" PEX TEE	25	800	<input type="checkbox"/>
H60061	HPPEXLFT341212	3/4" PEX x 1/2" PEX x 1/2" PEX TEE	25	800	<input type="checkbox"/>
H60062	HPPEXLFT341234	3/4" PEX x 1/2" PEX x 3/4" PEX TEE	25	400	<input type="checkbox"/>
H60063	HPPEXLFT343412	3/4" PEX x 3/4" PEX x 1/2" PEX TEE	25	400	<input type="checkbox"/>
H60064	HPPEXLFT34	3/4" PEX x 3/4" PEX x 3/4" PEX TEE	25	400	<input type="checkbox"/>
H60066	HPPEXLFT1112	1" PEX x 1" PEX x 1/2" PEX TEE	5	120	<input type="checkbox"/>
H60067	HPPEXLFT1134	1" PEX x 1" PEX x 3/4" PEX TEE	5	120	<input type="checkbox"/>
H60065	HPPEXLFT13434	1" PEX x 3/4" PEX x 3/4" PEX TEE	5	120	<input type="checkbox"/>
H60086	HPPEXLFT1341	1" PEX x 3/4" PEX x 1" PEX TEE	5	120	<input type="checkbox"/>
H60068	HPPEXLFT1	1" PEX x 1" PEX x 1" PEX TEE	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): 320°F (160°C) **Maximum working temperature/pressure:** 320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤ 0.25% per the Safe Drinking Water Act (Sec. 1417) ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | MALE ADAPTER



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
MALE ADAPTER					
H60076	HPPEXLFMA12	1/2" PEX x 1/2" MIP MALE ADAPTER	25	800	<input type="checkbox"/>
H60077	HPPEXLFMA1234	1/2" PEX x 3/4" MIP MALE ADAPTER	25	400	<input type="checkbox"/>
H60078	HPPEXLFMA3412	3/4" PEX x 1/2" MIP MALE ADAPTER	25	400	<input type="checkbox"/>
H60079	HPPEXLFMA34	3/4" PEX x 3/4" MIP MALE ADAPTER	25	400	<input type="checkbox"/>
H60085	HPPEXLFMA134	1" PEX x 3/4" MIP MALE ADAPTER	5	120	<input type="checkbox"/>
H60080	HPPEXLFMA1	1" PEX x 1" MIP MALE ADAPTER	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): 320°F (160°C) **Maximum working temperature/pressure:** 320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act (Sec. 1417) ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | MALE SWEAT ADAPTER



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
MALE SWEAT ADAPTER					
H60043	HPPEXLFMSA12	1/2" PEX x 1/2" MALE SWEAT ADAPTER	25	800	<input type="checkbox"/>
H60044	HPPEXLFMSA34	3/4" PEX x 3/4" MALE SWEAT ADAPTER	25	400	<input type="checkbox"/>
H60045	HPPEXLFMSA1	1" PEX x 1" MALE SWEAT ADAPTER	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): 320°F (160°C) **Maximum working temperature/pressure:** 320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] amended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | FEMALE ADAPTER



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
FEMALE ADAPTER					
H60081	HPPEXLFFA12	1/2" PEX x 1/2" FIP FEMALE ADAPTER	25	400	<input type="checkbox"/>
H60084	HPPEXLFFA1234	1/2" PEX x 3/4" FIP FEMALE ADAPTER	25	400	<input type="checkbox"/>
H60082	HPPEXLFFA34	3/4" PEX x 3/4" FIP FEMALE ADAPTER	25	400	<input type="checkbox"/>
H60083	HPPEXLFFA1	1" PEX x 1" FIP FEMALE ADAPTER	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): 320°F (160°C) **Maximum working temperature/pressure:** 320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | FEMALE SWEAT ADAPTER



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
FEMALE SWEAT ADAPTER					
H60040	HPPEXLFFSA12	1/2" PEX x 1/2" FEMALE SWEAT ADAPTER	25	800	<input type="checkbox"/>
H60041	HPPEXLFFSA34	3/4" PEX x 3/4" FEMALE SWEAT ADAPTER	25	400	<input type="checkbox"/>
H60042	HPPEXLFFSA1	1" PEX x 1" FEMALE SWEAT ADAPTER	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): **Maximum working temperature/pressure:**

320°F (160°C)

320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] amended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

www.hydrapro.biz | (800) 849-4844 | Fax (877) 249-8435

Atlanta (GA) • Dallas (TX) • Houston (TX) • Pompano Beach (FL) • Jackson (MI)

BRASS PEX FITTINGS | PEX x POLYBUTYLENE ADAPTER



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
PEX x POLYBUTYLENE ADAPTER					
H60046	HPPEXLFPBT12	1/2" PEX x 1/2" POLYBUTYLENE ADAPTER	25	800	<input type="checkbox"/>
H60047	HPPEXLFPBT34	3/4" PEX x 3/4" POLYBUTYLENE ADAPTER	25	400	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): 320°F (160°C) **Maximum working temperature/pressure:** 320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | PLUG



Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
PLUG					
H60073	HPPEXLFP12	1/2" PEX PLUG	25	800	<input type="checkbox"/>
H60074	HPPEXLFP34	3/4" PEX PLUG	25	400	<input type="checkbox"/>
H60075	HPPEXLFP1	1" PEX PLUG	5	120	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada



Maximum temperature (no pressure): 320°F (160°C) **Maximum working temperature/pressure:** 320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act [Sec. 1417] ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:

JOB LOCATION:

CONTRACTOR:

DATE:

ITEM TAG:

ENGINEER APPROVAL:

DATE:

PART NUMBER:

BRASS PEX FITTINGS | CRIMP RING


Part #	Model #	Description (Size)	Inner Carton Qty	Master Carton Qty	MAKE SELECTION BELOW
CRIMP RING					
H60051	HPPEXLFCR12	1/2" CRIMP RING	100	1000	<input type="checkbox"/>
H60052	HPPEXLFCR34	3/4" CRIMP RING	100	1000	<input type="checkbox"/>
H60053	HPPEXLFCR1	1" CRIMP RING	50	500	<input type="checkbox"/>

STANDARDS

CAN/CSA B137.5; ASTM F877; ASTM F1960

CODES

IPC; UPC; NSPC; NPC of Canada


Maximum temperature (no pressure): **Maximum working temperature/pressure:**

320°F (160°C)

320°F (160°C)

- Lead-Free* Brass
- Manufactured to ASTM Standard F1807

* Lead Free refers to the wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$ per the Safe Drinking Water Act (Sec. 1417) ammended 1-4-2011 and other equivalent state regulations.

JOB NAME:
JOB LOCATION:
CONTRACTOR:
DATE:
ITEM TAG:
ENGINEER APPROVAL:
DATE:
PART NUMBER:
www.hydrapro.biz | (800) 849-4844 | Fax (877) 249-8435

Atlanta (GA) • Dallas (TX) • Houston (TX) • Pompano Beach (FL) • Jackson (MI)